



US008548135B1

(12) **United States Patent**
Lavian et al.

(10) **Patent No.:** **US 8,548,135 B1**
(45) **Date of Patent:** **Oct. 1, 2013**

(54) **SYSTEMS AND METHODS FOR VISUAL PRESENTATION AND SELECTION OF IVR MENU**

(76) Inventors: **Tal Lavian**, Sunnyvale, CA (US); **Zvi Or-Bach**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 333 days.

(21) Appl. No.: **13/022,869**

(22) Filed: **Feb. 8, 2011**

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/699,618, filed on Feb. 3, 2010.

(51) **Int. Cl.**
H04M 11/00 (2006.01)

(52) **U.S. Cl.**
USPC **379/93.25**; 379/93.17; 379/142.06

(58) **Field of Classification Search**
USPC 379/93.17, 93.23, 142.06, 142.15, 379/142.16

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,653,045 A	3/1987	Stanley et al.
4,736,405 A	4/1988	Akiyama
4,897,866 A	1/1990	Majmudar et al.
5,006,987 A	4/1991	Harles
5,007,429 A	4/1991	Treach et al.
5,027,400 A	6/1991	Baji et al.
5,086,385 A	2/1992	Launey et al.
5,144,548 A	9/1992	Salandro
5,265,014 A	11/1993	Haddock et al.
5,294,229 A	3/1994	Hartzell et al.

5,335,276 A	8/1994	Thompson et al.
5,416,831 A	5/1995	Chewning, III et al.
5,417,575 A	5/1995	McLaggart
5,422,809 A	6/1995	Griffin et al.
5,465,213 A	11/1995	Ross
5,465,401 A	11/1995	Thompson
5,475,399 A	12/1995	Borsuk
5,499,330 A	3/1996	Lucas et al.
5,519,809 A	5/1996	Husseiny et al.
5,533,102 A	7/1996	Robinson et al.
5,550,746 A	8/1996	Jacobs
5,572,581 A	11/1996	Sattar et al.
5,585,858 A	12/1996	Harper et al.
5,586,235 A	12/1996	Kauffman
5,588,044 A	12/1996	Lofgren et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP	1225754 A3	7/2003
EP	1001597 A3	9/2003

(Continued)

OTHER PUBLICATIONS

Yin, M. and Zhai, S., "The Benefits of Augmenting Telephone Voice Menu Navigation with Visual Browsing and Search," CHI'06 Proceedings of the SIGCHI conference on Human Factors in computing systems: pp. 319-328, ACM, Montreal, Canada (Apr. 2006).


(Continued)

Primary Examiner — Stella Woo

(57) **ABSTRACT**

Embodiments of the invention provide a communication device. The communication device comprises a database comprising one or more visual IVR menus associated with a plurality of calling devices. Further, the communication device comprises means for receiving a call from a phone number of a calling device, and means for displaying a visual IVR menu associated with the phone number of the calling device.

18 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,592,538 A	1/1997	Kosowsky et al.	6,529,500 B1	3/2003	Pandharipande
5,606,361 A	2/1997	Davidsohn et al.	6,560,320 B1	5/2003	Paleiov et al.
5,633,909 A	5/1997	Fitch	6,603,840 B2	8/2003	Fellingham et al.
5,633,916 A	5/1997	Goldhagen et al.	6,606,611 B1	8/2003	Khan
5,657,221 A	8/1997	Warman et al.	6,606,741 B2	8/2003	Kojima et al.
5,689,648 A	11/1997	Diaz et al.	6,636,835 B2	10/2003	Ragsdale et al.
5,724,412 A	3/1998	Srinivasan	6,653,930 B1	11/2003	Bonomo et al.
5,739,814 A	4/1998	Ohara et al.	6,658,389 B1	12/2003	Alpdemir
5,740,549 A	4/1998	Reilly et al.	6,705,869 B2	3/2004	Schwartz
5,768,142 A	6/1998	Jacobs	6,714,519 B2	3/2004	Luzzatti et al.
5,790,652 A	8/1998	Gulley et al.	6,731,625 B1	5/2004	Easteop et al.
5,794,205 A	8/1998	Walters et al.	6,754,181 B1	6/2004	Elliott et al.
5,796,806 A	8/1998	Birckbichler	6,788,770 B1	9/2004	Cook et al.
5,802,283 A	9/1998	Grady et al.	6,791,583 B2	9/2004	Tang et al.
5,802,526 A	9/1998	Fawcett et al.	6,816,580 B2	11/2004	Timmins
5,807,336 A	9/1998	Russo et al.	6,820,037 B2	11/2004	Simon
5,819,225 A	10/1998	Eastwood et al.	6,820,062 B1	11/2004	Gupta et al.
5,822,404 A	10/1998	Cave	6,826,194 B1	11/2004	Vered et al.
5,822,405 A	10/1998	Astarabadi	6,829,368 B2	12/2004	Meyer et al.
5,838,682 A	11/1998	Dekelbaum et al.	6,856,673 B1	2/2005	Banks et al.
5,838,775 A	11/1998	Montalbano	6,862,713 B1	3/2005	Kraft et al.
5,867,816 A	2/1999	Nussbaum	6,865,268 B1	3/2005	Matthews et al.
5,873,068 A	2/1999	Beaumont et al.	6,885,737 B1	4/2005	Gao et al.
5,885,083 A	3/1999	Ferrell	6,889,195 B2	5/2005	Strandberg
5,885,245 A	3/1999	Lynch et al.	6,920,205 B2	7/2005	Hahn et al.
5,890,123 A	3/1999	Brown et al.	6,920,425 B1	7/2005	Will et al.
5,892,813 A	4/1999	Morin et al.	6,920,431 B2	7/2005	Showghi et al.
5,907,793 A	5/1999	Reams	6,937,705 B1	8/2005	Godfrey et al.
5,912,952 A	6/1999	Brendzel	6,968,506 B2	11/2005	Yacovone et al.
5,913,195 A	6/1999	Weeren et al.	6,990,455 B2	1/2006	Vozick
5,920,477 A	7/1999	Hoffberg et al.	7,006,612 B1	2/2006	Stroud et al.
5,937,040 A	8/1999	Wrede et al.	7,020,609 B2	3/2006	Thrift et al.
5,940,488 A	8/1999	DeGrazia et al.	7,027,990 B2	4/2006	Sussman
5,948,040 A	9/1999	DeLorme et al.	7,036,128 B1	4/2006	Julia et al.
5,956,034 A	9/1999	Sachs et al.	7,039,589 B2	5/2006	Whitham
5,982,875 A	11/1999	Lieben et al.	7,047,196 B2	5/2006	Calderone et al.
5,987,103 A	11/1999	Martino	7,065,188 B1	6/2006	Mei et al.
6,009,398 A	12/1999	Mueller et al.	7,068,643 B1	6/2006	Hammond
6,014,428 A	1/2000	Wolf	7,092,738 B2	8/2006	Creamer et al.
6,020,915 A	2/2000	Bruno et al.	7,100,118 B1	8/2006	Klask
6,049,779 A	4/2000	Berkson	7,130,391 B2	10/2006	Janakiraman et al.
6,055,513 A	4/2000	Katz et al.	7,136,480 B2	11/2006	Mason
6,062,863 A	5/2000	Kirksey et al.	7,139,591 B2	11/2006	Callaghan et al.
6,088,429 A	7/2000	Garcia	7,145,902 B2	12/2006	Schindler et al.
6,088,712 A	7/2000	Huang et al.	7,146,321 B2	12/2006	Cyr et al.
6,091,805 A	7/2000	Watson	7,149,549 B1	12/2006	Ortiz et al.
6,091,956 A	7/2000	Hollenberg	7,159,008 B1	1/2007	Wies et al.
6,104,790 A	8/2000	Narayanawami	7,177,814 B2	2/2007	Gong et al.
6,144,848 A	11/2000	Walsh et al.	7,180,889 B1	2/2007	Kung et al.
6,148,065 A	11/2000	Katz	7,180,985 B2	2/2007	Colson et al.
6,169,734 B1	1/2001	Wilson	7,181,401 B2	2/2007	Johnson et al.
6,212,547 B1	4/2001	Ludwig et al.	7,181,502 B2	2/2007	Incertis
6,228,921 B1	5/2001	Kasemann et al.	7,188,352 B2	3/2007	Nathan et al.
6,229,694 B1	5/2001	Kono	7,203,517 B2	4/2007	Shimoda et al.
6,230,197 B1	5/2001	Beck et al.	7,206,745 B2	4/2007	Surukkai et al.
6,259,444 B1	7/2001	Palmer et al.	7,206,809 B2	4/2007	Ludwig et al.
6,263,064 B1	7/2001	O'Neal et al.	7,209,124 B2	4/2007	Hunt et al.
6,273,726 B1	8/2001	Kirksey et al.	7,213,061 B1	5/2007	Hite et al.
6,285,364 B1*	9/2001	Giordano et al. 715/804	7,215,743 B2	5/2007	Creamer et al.
6,321,198 B1	11/2001	Hank et al.	7,216,348 B1	5/2007	deCarmo
6,335,678 B1	1/2002	Heutschi	7,225,409 B1	5/2007	Schnarel et al.
6,366,650 B1	4/2002	Rhie et al.	7,225,455 B2	5/2007	Bennington et al.
6,373,817 B1	4/2002	Kung et al.	7,228,492 B1	6/2007	Graham
6,400,807 B1	6/2002	Hewitt et al.	7,231,636 B1	6/2007	Evans
6,405,033 B1	6/2002	Kennedy, III et al.	7,231,656 B1	6/2007	Nathan
6,408,301 B1	6/2002	Patton et al.	7,240,006 B1	7/2007	Brocius et al.
6,427,063 B1	7/2002	Cook et al.	7,240,289 B2	7/2007	Naughton et al.
6,445,694 B1	9/2002	Swartz	7,246,063 B2	7/2007	James et al.
6,449,595 B1	9/2002	Arslan et al.	7,248,885 B2	7/2007	Benco et al.
6,456,706 B1	9/2002	Blood et al.	7,250,939 B2	7/2007	Lira
6,460,057 B1	10/2002	Butler et al.	7,254,227 B2	8/2007	Mumick et al.
6,463,145 B1	10/2002	O'Neal et al.	7,265,861 B1	9/2007	Ranalli et al.
6,482,156 B2	11/2002	Iliff	7,266,185 B2	9/2007	Trandal et al.
6,505,146 B1	1/2003	Blackmer	7,266,186 B1	9/2007	Henderson
6,510,411 B1	1/2003	Norton et al.	7,266,499 B2	9/2007	Surace et al.
			7,272,222 B2	9/2007	Joseph et al.
			7,272,497 B2	9/2007	Koshiji et al.
			7,277,854 B2	10/2007	Bennett et al.
			7,280,097 B2	10/2007	Chen et al.

7,280,646 B2 10/2007 Urban et al.
 7,280,651 B2 10/2007 Anderson
 7,286,990 B1 10/2007 Edmonds et al.
 7,289,608 B2 10/2007 Kumhyr
 7,289,904 B2 10/2007 Uyeki
 7,299,405 B1 11/2007 Lee et al.
 7,303,121 B2 12/2007 Martinez
 7,319,477 B2 1/2008 Katz
 7,324,947 B2 1/2008 Jordan et al.
 7,328,239 B1 2/2008 Berberian et al.
 7,330,890 B1 2/2008 Partovi et al.
 7,353,016 B2 4/2008 Roundtree et al.
 7,392,193 B2 6/2008 Mault
 7,398,215 B2 7/2008 Mesbah et al.
 7,406,413 B2 7/2008 Geppert et al.
 7,412,533 B1 8/2008 Johnson et al.
 7,433,452 B2 10/2008 Taylor et al.
 7,440,898 B1 10/2008 Eberle et al.
 7,450,112 B2 11/2008 Shneidman
 7,466,803 B2 12/2008 Burg et al.
 7,492,883 B2 2/2009 Kumhyr
 7,539,484 B2 5/2009 Roundtree
 7,546,143 B2 6/2009 Nelson et al.
 7,584,249 B2 9/2009 Mummick et al.
 7,606,741 B2 10/2009 King et al.
 7,646,858 B2 1/2010 Salafia et al.
 7,693,720 B2 4/2010 Kennewick et al.
 7,720,091 B2 5/2010 Faber et al.
 7,729,490 B2 6/2010 Hemm et al.
 7,757,173 B2 7/2010 Beaman
 7,809,376 B2 10/2010 Letourneau et al.
 7,813,485 B2 10/2010 Yin et al.
 7,843,899 B2 11/2010 Burritt
 7,864,944 B2 1/2011 Khouri et al.
 7,908,381 B2 3/2011 Koch et al.
 7,966,188 B2 6/2011 Ativanichayaphong et al.
 8,000,454 B1 8/2011 Or-Bach et al.
 8,023,624 B2 9/2011 Kargman et al.
 8,054,952 B1 11/2011 Or-Bach et al.
 8,155,280 B1 4/2012 Or-Bach et al.
 8,160,215 B2 4/2012 Or-Bach et al.
 8,374,319 B1* 2/2013 Bridges et al. 379/88.22
 2002/0055844 A1 5/2002 L'Esperance et al.
 2002/0147986 A1 10/2002 Michael et al.
 2003/0005126 A1 1/2003 Schwartz et al.
 2003/0007625 A1 1/2003 Pines et al.
 2003/0033382 A1 2/2003 Bogolea et al.
 2003/0074198 A1 4/2003 Sussman
 2003/0112931 A1 6/2003 Brown et al.
 2004/0034561 A1 2/2004 Smith
 2004/0122941 A1 6/2004 Creamer et al.
 2004/0198316 A1 10/2004 Johnson
 2004/0204116 A1 10/2004 Ben Efraim et al.
 2005/0004977 A1 1/2005 Roberts et al.
 2005/0055310 A1 3/2005 Drewett et al.
 2006/0148459 A1 7/2006 Wolfman et al.
 2006/0203977 A1 9/2006 Erhart et al.
 2006/0239422 A1 10/2006 Rinaldo et al.
 2006/0259424 A1 11/2006 Turcotte et al.
 2006/0262921 A1 11/2006 Eppel et al.
 2006/0285662 A1 12/2006 Yin et al.
 2007/0026852 A1 2/2007 Logan et al.
 2007/0032247 A1 2/2007 Shaffer et al.
 2007/0038513 A1 2/2007 Flax et al.
 2007/0094109 A1 4/2007 Perry
 2007/0123223 A1 5/2007 Letourneau et al.
 2007/0239537 A1 10/2007 Protheroe et al.
 2007/0243887 A1 10/2007 Bandhole et al.
 2007/0298776 A1 12/2007 Arlene
 2008/0066015 A1 3/2008 Blankenhorn
 2008/0095330 A1 4/2008 Jin et al.
 2008/0226042 A1 9/2008 Singh
 2008/0250334 A1 10/2008 Price
 2009/0041215 A1 2/2009 Schmitt et al.
 2009/0116414 A1 5/2009 Or et al.
 2009/0136014 A1 5/2009 Bigue et al.
 2009/0154666 A1 6/2009 Rios et al.
 2009/0202050 A1 8/2009 Berger et al.
 2009/0207980 A1 8/2009 Berger et al.

2009/0207996 A1 8/2009 Berger et al.
 2009/0225788 A1 9/2009 Kephart et al.
 2009/0228908 A1 9/2009 Margis et al.
 2009/0276441 A1 11/2009 Malik
 2009/0276708 A1 11/2009 Smith et al.
 2009/0280863 A1 11/2009 Shin et al.
 2009/0285380 A1 11/2009 Chen et al.
 2010/0007028 A1 1/2010 Fachmann et al.
 2010/0021030 A1 1/2010 Collins et al.
 2010/0049654 A1 2/2010 Pilo et al.
 2010/0087175 A1 4/2010 Roundtree
 2010/0100377 A1 4/2010 Madhavapeddi et al.
 2010/0166158 A1 7/2010 Costello et al.
 2010/0172481 A1 7/2010 Canu et al.
 2010/0189250 A1 7/2010 Williams et al.
 2010/0191608 A1 7/2010 Mikkelsen et al.
 2011/0009096 A1 1/2011 Rotsztein et al.
 2011/0014952 A1 1/2011 Minton
 2011/0060683 A1 3/2011 Salmon Rock et al.
 2011/0091021 A1 4/2011 Adkar et al.
 2011/0099116 A1 4/2011 Gabel
 2011/0276408 A1 11/2011 Toole
 2012/0063574 A1 3/2012 Or-Bach et al.

FOREIGN PATENT DOCUMENTS

EP 1351477 A1 10/2003
 EP 1120954 A3 6/2005
 EP 1545101 A3 12/2005
 EP 774853 B1 5/2006
 EP 1874018 A1 1/2008
 JP 2004274425 A 9/2004
 WO 9819259 A1 5/1998
 WO 9840826 A3 12/1998
 WO 9856158 A3 3/1999
 WO 9848551 A3 4/1999
 WO 0131497 A1 5/2001
 WO 0157851 A1 8/2001
 WO 0165871 A1 9/2001
 WO 9820409 A8 11/2001
 WO 0217604 A1 2/2002
 WO 2004049306 A1 6/2004
 WO 2004064299 A3 7/2005
 WO 2007012831 A1 2/2007
 WO 2007081929 A3 1/2008
 WO 2008086320 A1 7/2008
 WO WO 2008/086320 A1 7/2008
 WO 2009006173 A3 3/2009
 WO 2009100477 A1 8/2009

OTHER PUBLICATIONS

Damhuis, M., et al., "A Multimodal Consumer Information Server with IVR Menu," 2nd IEEE Workshop on Interactive Voice Technology for Telecommunications Applications (IVTTA94): pp. 73-76, Kyoto, Japan (Sep. 1994).
 Shah, S.A.A., et al., "Interactive Voice Response with Pattern Recognition Based on Artificial Neural Network Approach," International Conference on Emerging Technologies: pp. 249-252, (Nov. 2007).
 Trihandoyo, A., et al., "A real-time speech recognition architecture for a multi-channel interactive voice response system," International Conference on Acoustics, Speech, and Signal Processing vol. 4: pp. 2687-2690,(1995).
 Hattori, S., et al., "A multimedia intelligent message communication system for distributed coordination environments," Electronics & Communications in Japan, Part I—Communications, vol. 76, No. 1, pp. 11-23 (1993).
 Patent abstracts of Japan, vol. 097, No. 001, Jan. 31, 1997 & JP 08 242307 A (Canon Inc), Sep. 17, 1996.
 Kalva, H., et al., "Delivering Object-Based Audio-Visual Services," IEEE Transactions on Consumer Electronics, vol. 45, No. 4, pp. 1108-1111, (1999).
 Schmandt, "Phoneshell: the telephone as computer terminal," Proceedings of first ACM International Conference on Multimedia, Anaheim, CA, US, pp. 373-381, (1993).
 Himberg, J., et al., "Time Series Segmentation for Context Recognition in Mobile Devices", IEEE, 203-210, (2001).

- Chris Schmandt and Stephen Casner, "Phonetool: Integrating Telephones and Workstations," IEEE Communication Society, Nov. 27-30, pp. 0970-0974, (1989).
- Basinger, R. G., et al., "Calling Card Service—Overall Description and Operational Characteristics", The Bell System Technical Journal, (1982).
- Cadiz et al. "Designing and Deploying an Information Awareness interface" CSCW'02, Nov. 2002, ACM, pp. 314-323.
- Corcoran et al. disclose "User interface technologies for home appliances and networks", IEEE Trans. Consumer Elect; pp. 679-685, (1998).
- Nancy Friedrich, "Graphical-User-Interface Module Eases Integration," Wireless Systems Design, Oct. 2004, 1 page.
- Balachandran, R., et al., "Dialog System for Mixed Initiative One-Turn Address entry and Error Recovery," Proceedings of SIGDIAL 2009, the 10th Annual Meeting of the Special Interest Group in Discourse and Dialogue, pp. 152-155, Queen Mary University of London, Association of Computational Logistics, (2009).
- Damhuis, M., et al., "A Multimodal Consumer Information Server with IVR Menu," *2nd IEEE Workshop on Interactive Voice Technology for Telecommunications Applications (IVTTA94)*: pp. 73-76, Kyoto, Japan (Sep. 1994).
- Trihandoyo, A., et al., "A real-time speech recognition architecture for a multi-channel interactive voice response system," *International Conference on Acoustics, Speech, and Signal Processing* vol. 4: pp. 2687-2690, (1995).
- Co-pending U.S. Appl. No. 12/699,618, inventors Lavian, T. and Or-Bach, Z., filed Feb. 3, 2010, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 12/707,714, inventors Lavian, T. and Or-Bach, Z., filed Feb. 18, 2010, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 12/719,001, inventors Lavian, T. and Or-Bach, Z., filed Mar. 7, 2010, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 12/879,318, inventors Lavian, T. and Or-Bach, Z., filed Mar. 7, 2010, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 12/022,883, inventors Lavian, T. and Or-Bach, Z., filed Feb. 8, 2011, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 13/113,825, inventors Lavian, T. and Or-Bach, Z., filed May 23, 2011, entitled "Portable universal communication device."
- Co-pending U.S. Appl. No. 13/022,851, inventors Lavian, T. and Or-Bach, Z., filed Feb. 8, 2011, entitled "Device and method for providing enhanced telephony."
- Co-pending U.S. Appl. No. 13/022,768, inventors Lavian, T. and Or-Bach, Z., filed Feb. 8, 2011, entitled "Device and method for providing enhanced telephony."
- Co-pending U.S. Appl. No. 13/022,909, inventors Lavian, T. and Or-Bach, Z., filed Feb. 8, 2011, entitled "Device and method for providing enhanced telephony."
- Co-pending U.S. Appl. No. 13/046,532, inventors Lavian, T. and Or-Bach, Z., filed Mar. 11, 2011, entitled "Systems and methods for communicating with an interactive voice response system."
- Co-pending U.S. Appl. No. 13/159,093, inventors Lavian, T. and Or-Bach, Z., filed Jun. 13, 2011, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 13/185,027, inventors Lavian, T. and Or-Bach, Z., filed Jul. 18, 2011, entitled "Systems and methods for visual presentation and selection of IVR menu."
- Co-pending U.S. Appl. No. 13/186,984, inventors Lavian, T. and Or-Bach, Z., filed Jul. 20, 2011, entitled "Systems and methods for visual presentation and selection of IVR menu."

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7

1

SYSTEMS AND METHODS FOR VISUAL PRESENTATION AND SELECTION OF IVR MENU

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a Continuation-In-Part (CIP) of U.S. Non-Provisional application Ser. No. 12/699,618 entitled 'Systems and methods for visual presentation and selection of IVR menu' and filed on Feb. 3, 2010.

FIELD OF THE INVENTION

The invention relates to Interactive Voice Response (IVR) system and more specifically the invention relates to presentation of a visual IVR menu of a calling first party device.

BACKGROUND OF THE INVENTION

The advent of Interactive Voice Response (IVR) systems has reduced operating costs for many types of businesses for providing services. Generally, the IVR systems allow a user to interact with an audio or visual response system. The IVR systems can provide prompts to a user and receive touch tone and/or spoken responses on the prompts from the user. Through such IVR dialogue the system collects sufficient information about the user to direct the call to the most appropriate resource, information processing system or the like.

In particular, the IVR Systems have allowed telephone service providers to host call centers for various businesses such as banks, insurance companies, restaurants, and other service providers. An objective of implementing the IVR systems is to provide the users or customers with a quick and good experience. Usually, the customer care executives/agents or audio IVR systems associated with the service providers call users of communication devices to offer or sell their services or products. When a user at a communication device receives a call from the agents or the audio IVR system, the user may not know the purpose of the call. Further, the user receiving the call may not know about the services provided by the calling service provider. Therefore, the user may have to listen to the calling service provider patiently and completely to know the purpose of the call and to know about their various services. Further, the desire to inquire about various other services of the service provider. This whole process may be time consuming and sometimes may be frustrating for the user.

Sometimes, it may be possible that the calling service provider does not include the information or resource desired by the user. Therefore, even after listening to the agent or audio IVR system, the user may not get the desired information. In such a case, either the user may have to wait for long time or contact some other service provider.

Some existing techniques try to address this problem by providing visual form of IVR. These techniques display the IVR menu graphically on a caller device. U.S. Pat. No. 7,215,743 assigned to International Business Machines Corporation and a published U.S. patent application with Ser. No. 11/957,605, filed Dec. 17, 2007 and assigned to Motorola Inc., provides the IVR menu of the first party device in a visual form to the caller. The caller can select the options from the IVR menu without listening to the complete audio IVR menu. However, the IVR menu displayed on the caller device is stored on an IVR server of a call receiving or service provider end. As a result, the visual IVR menu is specific to the call receiving end and only the IVR of the call receiving

2

end is displayed. These techniques therefore, require each call receiving end to set-up hardware, software and other facilities to be deployed for providing visual IVR servers. Moreover, the visual form of audio IVR menu is displayed only when the caller dials and connects to the IVR at service provider's end.

In the light of the above discussion, techniques are desired for providing enhanced telephony.

SUMMARY

Embodiments of the present invention provide a communication device. The communication device comprises a database comprising one or more visual Interactive Voice Response (IVR) menus associated with each of a plurality of phone numbers of first party devices. Further, the communication device comprises means for receiving a call from a phone number of a first party device; and means for displaying a visual IVR menu associated with the phone number of the first party device.

Embodiments of the present invention provide a communication device. The communication device comprises a processor. Further, the communication device comprises a memory coupled to the processor. The memory comprises a database comprising one or more visual IVR menus associated with each of a plurality of phone numbers of first party devices. Further, the memory comprises instructions executable by the processor for receiving a call from a phone number of a first party device, and for displaying a visual IVR menu associated with the phone number of the first party device.

An aspect of the invention is to provide a communication device for displaying a visual IVR menu of a phone number of a first party device. The communication device receives a call from the first party device. The communication device is further configured to display one or more communication options.

Embodiments of the present invention provide a method for providing enhanced telephony. The method comprises receiving, at a communication device, a call from a phone number of a first party device. The communication device comprises one or more visual IVR menus associated with each of a plurality of phone numbers of first party devices. Further, the method comprises displaying, at the communication device, a visual IVR menu associated with the phone number of the first party device.

An aspect of the present invention is to provide a method for displaying, at a communication device, a visual IVR menu of a phone number of a calling first party device. Further, the method displays one or more communication options at the communication device.

Another aspect of the invention is to enable a user at the communication device to interact with the visual IVR menu of the calling first party device without listening to the audible IVR menu of the first party device.

Yet another aspect of the invention is to provide the visual IVR menu of a first party device to a user of a communication device before establishing a communication session between the communication device and the first party device.

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

FIG. 1A illustrates an exemplary environment where various embodiments of the invention function;

FIG. 1B illustrates another exemplary environment where various embodiments of the invention function;

FIG. 1C illustrates yet another exemplary environment where various embodiments of the invention function;

FIG. 2 illustrates yet another exemplary environment where various embodiments of the invention functions;

FIG. 3 illustrates an exemplary visual IVR menu along with one or more communication options at a communication device, in accordance with an embodiment of the invention;

FIGS. 4A and 4B illustrates exemplary components of the device for implementing a Visuphone, in accordance with an embodiment of the invention;

FIG. 5 illustrates exemplary components of the device for implementing the Visuphone, in accordance with another embodiment of the invention;

FIG. 6 illustrates the presentation of the visual IVR menu when a phone connection is associated with a wide band internet 'smart' modem; and

FIG. 7 illustrates a flowchart diagram for providing enhanced telephony, in accordance with an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

Illustrative embodiments of the invention now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the invention are shown. Indeed, the invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout.

FIG. 1A illustrates an exemplary environment where various embodiments of the invention function. A communication network 100 may include a plurality of first party devices 102a-n. Further, the communication network 100 may include communication device 104a. A person skilled in art will appreciate, that the communication network 100 may also include more than one communication devices. Examples of the communication network 100 include, but are not limited to, the Internet, PSTN, Local Area Network (LAN), Wide Area Network (WAN), Metropolitan Area Network (MAN), and so forth. The first party devices 102a-n may initiate a call to connect to the communication device 104a. Each of the first party devices 102a-n may have associated one or more phone numbers. The first party devices 102a-n can be a device capable of data/voice communication. Examples of the first party devices 102a-n include, but are not limited to, a telephone, a computer, a laptop computer, a personal digital assistant (PDA), a mobile phone, and so forth. In an embodiment, each of the first party devices 102a-n may include one or more audio/visual Interactive Voice Response (IVR) menus. Various types of the first party devices 102a-n that implement the audible IVR menu include, for example, banks, hotels, fast-food outlets, utility services providers, corporate offices, mobile phone service providers, hospitals and so forth. Typically, the audible IVR menu provided by the first party devices 102a-n comprises audible options or instructions. In an embodiment, the visual IVR menu includes one or more text and/or graphical representation of different nodes corresponding to different nodes of the audio IVR menu.

Further, the IVR menu of a first party device such as the first party device 102a can be different from another first party device such as the first party device 102c. For example, IVR menus of a hospital may be completely different from that of a bank. Each of the first party devices 102a-n may connect to the communication device 104a by dialing a phone number

associated with the communication device 104a. Further, each of the first party devices 102a-n can have more than one audio/visual IVR menus. Each of the first party devices 102a-n has an associated phone number. A user 108 may connect to a first party device of the first party devices 102a-n either by accepting a call from a first party device such as a first party device 102a or by dialing a phone number of the first party device 102a. After establishing a connection with the first party device 102a, the user 108 can interact with the first party device 102a via the IVR menu associated with the first party device 102a. Further, the first party devices 102a-n can send information to the communication device 104a. Similarly, the communication device 104a may also request information from the first party devices 102a-n. The communication device 104a can be a telecommunication device that can connect directly to a Public Switched Telephone Network (PSTN) 110. A person skilled in the art will appreciate, that the communication device 104a can also connect to a private telephone exchange. Examples of the communication device 104a include, but are not limited to, a telephone, a mobile phone, a smart phone or any other device capable of voice or data communication.

The communication device 104a includes a Visuphone 106 that may provide data regarding a phone number of the first party devices 102a-n from which the call is received at the communication device 104a. For example, the data may include geographical information or services provided by the first party devices 102a-n. Further, the Visuphone 106 may receive a call from a first party device 102a of first party devices 102a-n. In an embodiment, the Visuphone 106 may receive calls from the first party devices 102a-n. Further, the Visuphone 106 may display a visual IVR menu on the communication device 104a corresponding to the audible IVR menu based on a phone number of the first party device 102a from which the call has been received. In an embodiment, the Visuphone 106 may display the visual IVR menu at the communication device 104a even before accepting the call by the user 108. The visual IVR menu may have one or more options. Thereafter, the user 108 can select the options of the displayed visual IVR menu to obtain the required resource/information or service from the calling first party device 102a. Furthermore, the Visuphone 106 may display one or more communication options on a screen of the communication device 104a. Examples of the communication options include, but are not limited to, a conferencing option, a call forwarding option, a busy option, and so forth. The user 108 can select a communication option from the displayed one or more communication options. Based on the selection by the user a communication session may be established between the communication device 104a and the calling first party device 102a. In an embodiment, when the user 108 selects the 'conferencing' option, another communication device of the communication network 100 may be included in the call with the first party device 102a. The Visuphone 106 may be hardware, software, or a firmware implemented on the communication device 104a, or a combination thereof.

In an embodiment, the communication network 100 may include a server. The server may maintain the updated information of the first party devices 108a-n. In an embodiment of the invention, the communication device 104a can request and/or receive updates from the server. This may happen in a case when requested information is not available on the calling first party device. Further, the communication network 100 can include more than one communication devices. The communication device 104a may also request information from the first party device 102a from which the call is received.

FIG. 1B illustrates another exemplary environment where various embodiments of the invention function. As shown, a communication device **104b** can be a communication device that can be connected directly to network **114**. Examples of the communication device **104b** include, but are not limited to, a personal computer, a laptop, a mobile phone, a smart-phone, a fixed line telephone, a Voice Over Internet Protocol (VOIP) phone or other devices capable of voice or data communication. The communication device **104b** may include various applications or computer programs that enable the user **108** to use the communication device **104b** for receiving and/or accepting call from the first party devices **102a-n** through PSTN **110** over network **114** through a gateway **112**. For example, the applications may be VOIP applications, such as but not limited to, Skype, Magic Jack, Google Talk and so forth. Examples of the network **114** include any wired or wireless network, such as but not limited to, LAN, WAN, a Wi-Fi network and so forth. As discussed with reference to FIG. 1A, the first party devices **102a-n** presents the audible IVR to the communication device **104b**. As discussed with reference to FIG. 1A, the Visuphone **106** may receive a call from a phone number of a first party device **102a** of the first party devices **102a-n**. The Visuphone **106** may further display the visual IVR menu associated with the phone number of the first party device **102a**, from which call is received. Further, the Visuphone **106** may display the one or more communication options such as a call forwarding option on the screen of the communication device **104b**.

As shown, the communication device **104c** can be connected to the PSTN **110** through the network **114** or through the cellular network **116**. Various service providers provide multiple or overlapping services to customers. For example, cable television service provider may also provide phone and network service, optical network provider may also provide phone or television services, WiMax service providers that provide phone service and so forth. The network **114** may be any service provider that provides such services, for example, but not limited to, cell phone services, wireless services, network services, cable television services, or various combinations of the above or other type of services. As discussed with reference to FIG. 1A, the first party devices **102a-n** includes one or more audible IVR menus. The communication device **104c** includes the Visuphone **106** which displays data corresponding to phone number of the calling first party devices **102a-n**. Further, Visuphone **106** may display a visual IVR menu corresponding to audible IVR menu of the phone number of the first party devices **102a-n**. Moreover, the visual IVR menu is displayed when a call is received from the first party device **102** of the first party devices **102a-n**. Thereafter, the user **108** may accept the call from the first party device **102** to establish a communication session with the calling first party device **102**. In an embodiment of the invention, the Visuphone **106** may display one or more communication options at the communication device **104c**. The user **108** may select a communication option from the displayed communication options for interacting with the calling first party device **102**. In an embodiment, the Visuphone **106** may receive the visual IVR menu from the first party device **102**. In an embodiment, the calling first party device **102** may request the information requested by the Visuphone **106** or the user **108**, from the server of the communication network **100**. Thereafter, the calling first party device **102** may send the information received from the server to the Visuphone **106**. The Visuphone **106** may further request and/or receive information from the calling first party device **102**. Further, the Visuphone **106** may display the information at the communication device **104c**.

FIG. 2 illustrates yet another exemplary environment where various embodiments of the invention function. As discussed with reference to FIG. 1A, the communication network **100** includes the first party devices **102a-n** which may initiate a call to the phone number associated with the communication device **104a**. Further, the communication network **100** may include a second party device **202**. In an embodiment, the communication network **100** may include a plurality of second party devices. The communication device **104a** includes the Visuphone **106** that can receive the call from the first party device **102**. The Visuphone **106** may further display a visual IVR menu associated with the calling first party device **102**. In an embodiment, the Visuphone **106** may highlight an option or node in the visual IVR menu. The highlighted option represents the exact position of first party device **102** within the visual IVR menu from where the call is initiated. For example, in case of a bank, if a person from insurance department initiates a call to a mobile phone, then the node representing the insurance is highlighted in the visual IVR menu of the bank displayed at the mobile phone. Therefore, the user **108** can know exactly from which department within the organization the call is coming from. Accordingly, the user **108** may act or opt to attend or reject the call from the first party device **102**.

Further, the Visuphone **106** may display one or more communication options on a screen of the communication device **104a**. Examples of the one or more communication options can include, but are not limited to, a conferencing option, a call forwarding option, a busy option, and so forth. The user **108** may select an option from the displayed communication options. The Visuphone **106** may establish a connection with a second party device based on the selection of the communication option by the user **108**. The second party device **202** may be a communication device **104**, a first party device of the first party devices **102a-n**, a server, and so forth depending on the selection of the communication option. The second party device **202** may have an associated phone number.

In an embodiment, when the user **108** selects a 'conferencing' option from the displayed one or more communication options then a second party device **202** may be included in the call. Now the second party device **202**, the communication device **104a**, and the first party device **102** from which the call was received initially may communicate through a conference call and can interact with each other. Thereafter, all three types of devices in the conference call may further request or receive information from each other. In an embodiment, the second party device **202** may be another communication device of the communication network **100**. In an embodiment, the Visuphone **106** may further display a visual IVR menu associated with the second party **202**. In an embodiment, the Visuphone **106** of the communication device **104a** may receive the visual IVR menu associated with the phone number of the second party device **202**. In an exemplary scenario, a user receives a call at a first mobile phone from an executive of the insurance department of a bank. The user **108** may select a 'conferencing' option and can include another user of a second mobile phone who might be interested in knowing about the insurance policies offered by the executive. In an embodiment, the user **108** of the communication device **104a** may opt to leave the conference call in between of the call. Thereafter, the first party device **102** and second party device **202** may continue with the call.

In an embodiment, the user **108** may select a 'call forwarding' option of the displayed one or more communication options to forward the call coming from the first party device **102** to a second party **202**. Thereafter, a user of the second party device **202** may interact with the first party device **102**.

For example, when a user of first mobile phone receives a call from a pizzeria, then a visual IVR menu of the pizzeria can be displayed at the mobile phone along with various communication options. The user may forward the call to a second mobile phone by selecting the ‘call forwarding’ option. Now, the call will be between the second mobile phone and the pizzeria. In an embodiment, the second party device **202** may include a Visuphone. In another embodiment, the second party device **202** may include one or more audio and/or visual IVR menus. In an embodiment, a visual IVR menu associated with a phone number of the second party device **202** may be displayed on the communication device **104a**. Further, the Visuphone **106** may receive the visual IVR menu of the second party device from the second party device **202**.

FIG. 3 illustrates an exemplary visual IVR menu **302** along with one or more communication options at the communication device **104a**, in accordance with an embodiment of the invention. As discussed with reference to FIGS. 1A and 2, the Visuphone **106** may display the visual IVR menu **302** associated with the phone number of the calling first party device **102** on the screen of the communication device **104a**. The visual IVR menu is displayed with added graphics on the screen of the communication device **104a**. The visual IVR menu **302** may include one or more options corresponding to every node in the calling first party device **102**. It is well known that graphics are easier to learn and are faster to recognize than words. Therefore, graphics are used in various computerized device interfaces. Various types of graphics can be displayed for example, animated icons, icons that highlight or animate when the node is highlighted, and so forth. The graphics may be displayed for each node or a few nodes based on the usability of the visual IVR menu **302**. For example, for the node **310** an icon of a vegetable may be displayed to designate a vegetarian pizza, and for the node **316** of home delivery, an icon of house may be displayed. In an embodiment of the invention, the visual IVR menu **302** can be customized to display only the text, only the icons or both. Furthermore, the user **108** can suggest or use various icons based on his preferences. The visual IVR menu is specific to the first party device **102** from which call is received.

Further, each of the first party devices **102a-n** may have more than one audio IVR menus. Therefore, different visual IVR menu corresponding to the one or more audio IVR menus is possible for each of the first party devices **102a-n**. In an embodiment, the communication device **104a** may include more than one visual IVR menus for each first party device of the first party devices **102a-n** based on the time. Therefore, different visual IVR menus corresponding to a first party device **102** might be presented to the user **108** depending on the time of dialing to the first party device **102**. In an exemplary scenario, in a hotel, the food items in a daytime menu card may be different from a night menu card. Accordingly, the options in the visual IVR menu may differ. Therefore, the visual IVR menus for daytime and night can be different for the hotel. When the user **108** receives a call from the phone number of the hotel in daytime, a daytime visual IVR menu can be displayed at the communication device **104a**, and if the user **108** receives a call at night, a different menu can be displayed at the communication device **104a**. Therefore, a visual IVR menu of the hotel displayed at the communication device **104a** for a call received at 12:30 PM may be different than the visual IVR menu displayed for another call received at 6 PM.

Further, the Visuphone **106** may display the one or more communication options **320a-n** on the screen of the communication device **104a**. Examples of the one or more communication options **320a-n** include, but are not limited to, a

conferencing option, a call forwarding option, a busy option, and so forth. In an embodiment, when the user **108** selects a ‘busy’ option of the communication options **320a-n**, a text or audio message may be sent to the calling first party device **102**. For example, when a user receives a call from a bank and selects the ‘busy’ option from the displayed visual IVR menu of the calling bank, then a customized or predefined message such as “I am busy right now, so please call later” can be sent to the bank. In an embodiment, the message may be an audio message.

In an embodiment, when the user **108** accepts the call from the first party device **102**, a communication session is established between the communication device **104a** and the first party device **102** from which the call is received. After communication establishment, the Visuphone **106** of the communication device **104a** may request and/or receive information from the calling first party device **102**. In an embodiment, the user **108** may include the second party device **202** by selecting ‘conferencing’ option from the displayed communication options **320a-n**. Thereafter, the three devices i.e. the first party device **102**, the communication device **104a**, and the second party device **202** may have a conference call and can interact with each other. In an embodiment, the user **108** may include more than one second party device **202** in the conference call. In an embodiment, the second party **202** may include another communication device of the communication network **100** in the conference call. In another embodiment, the calling first party device such as the first party device **102a** may include another first party device such as a first party device **102b** in the conference call. In another embodiment, the first party device **102** from which call is received may connect the communication device **104a** to another first party device **102b** during the call.

FIGS. 4A and 4B illustrate exemplary components of the communication device **104a** for implementing the Visuphone **106**, in accordance with an embodiment of the invention. The communication device **104a** includes a system bus **426** to connect the various components. Examples of system bus **426** include several types of bus structures including a memory bus, a peripheral bus, or a local bus using any of a variety of bus architectures. As discussed with reference to FIG. 1A, the communication device **104a** can be a communication device such as computer, a smart-phone and so forth. The communication device **104a** can connect to PSTN **110** through a gateway **424**, which is connected to network **114** through a network interface **412**. Input/Output (IO) interface **414** of the communication device **104a** may be configured to connect external or peripheral devices such as a memory card **416**, a keyboard **418**, a Universal Serial Bus (USB) device **420** and a mouse **422**. Although not shown, various other devices can be connected through IO interface **4104** to the communication device **104a**. In an embodiment of the invention, the communication device **104a** may be connected to a hub that provides various services such as voice communication, network access, television services and so forth. For example, the hub may be a Home Gateway device that acts as a hub between the home environment and the Broadband Network.

The communication device **104a** includes a display **402** to output graphical information to the user **108**. In an embodiment of the invention, the display **402** may include a touch sensitive screen. Therefore, the user **108** can provide inputs to the communication device **104a** by touching display **402** or by point and click using the ‘mouse’. Memory **406** of the communication device **104a** stores various programs, data and/or instructions that can be executed by a processor **404**. Examples of the memory **406** include, but are not limited to, a Random Access Memory (RAM), a Read Only Memory

(ROM), a hard disk, and so forth. A person skilled in the art will appreciate that other types of computer-readable media which can store data that is accessible by a computer, such as magnetic cassettes, flash memory cards, digital video disks, and the like, may also be used by the communication device **104a**. The memory **406** may include Operating System (OS) (not shown) for the communication device **104a** to function. Further, the memory **406** may include other applications that enable the user **108** to communicate/interact with the first party devices **102a-n**. Examples of other applications include, but are not limited to, Skype, Google Talk, Magic Jack, and so forth. Other applications may be stored as software or firmware on the communication device **104a**.

Further, the memory **406** includes the Visuphone **106** for providing a visual representation of the first party devices **102a-n**. As discussed with reference to the FIG. 1A, the Visuphone **106** may be hardware, a software or a firmware stored on the communication device **104a**. In an embodiment, the Visuphone **106** may be implemented as plug-in to other applications. The visual IVR menus are stored in a database **414** in memory **406** of the communication device **104a**. In an embodiment, the Visuphone **106** may receive updates about visual IVR menus from the server of the communication network **100** at predefined time. The predefined time may be for example, once a week, once a month, or any other interval predefined by the user **108** or the Visuphone **106**.

In an embodiment, the Visuphone **106** may display a visual IVR menu associated with the calling first party device before accepting the call by the user **108**. In an embodiment, the Visuphone **106** may display one or more communication options on the display **402** of the communication device **104a**. The communication option may be selected by the user **108** to include one or more second party **202** in the call.

The user **108** may input one or more key or key combinations using the keyboard **418**. The keyboard **418** may be a physical keyboard or a virtual keyboard displayed on a touch screen display **402**. In an embodiment, the keyboard **418** is a keypad on the communication device **104a**. Subsequently, after some processing by the Visuphone **106**, the visual IVR menu **302** corresponding to calling first party device phone number is searched and displayed on display **402**.

In an embodiment of the invention, the visual IVR menu may be provided in real-time to user. In an embodiment of the invention, the visual IVR menu is provided by a messaging service such as a Short Messaging Service (SMS). Therefore, first party devices may provide customized visual IVR menu to the user **108**. The visual IVR menu may be customized based on the profile of user. In an embodiment of the invention, the profile may be generated based on access pattern of user or the data capture by a hub connected to the communication device **104a**.

The user **108** can interact with the visual IVR menu by pressing a desired button from the keyboard **418**. For example, the user **108** can press a '3' key from the keyboard **418** to select a node **3** in the visual IVR menu **302**. Further, the user **108** can directly select the node **3** of the visual IVR menu **302** from the display **402**, in case of a touch sensitive screen. Depending on the complexity or size of first party devices, visual IVR menu **302** may have various nodes. Moreover, display area of the display **402** may be limited or small. As a result, all the nodes of the visual IVR menu **302** may not be displayed together on the display **402**. In such a case, the Visuphone **106** is configured to allow the user **108** to navigate by scrolling horizontally and/or vertically to view nodes on the visual IVR menu **302**. Further, the Visuphone **106** may detect the capability of the communication device **104a** before displaying the visual IVR menu **302**. For example, in

case the communication device **104a** is a basic mobile phone with limited functionality of the display screen. Therefore, the Visuphone **106** may display the visual IVR menu in form of a simple list. Similarly, a list may be displayed in case of fixed line or wired telephones. Moreover, in case the communication device **104a** includes a high capability screen, such as but not limited to an iPhone, then the visual IVR menu is displayed in form of graphics. Subsequently, after the user **108** selects a desired option or communication option from the visual IVR menu **302**, a connection is established between the communication device **104a** and the calling first party device. In one embodiment, the Visuphone **106** is configured to detect and present an application or computer program available on the communication device **104a**.

In an embodiment, the user **108** may dial a phone number from a VOIP application **428** on the communication device **104b**, as shown with reference to FIG. 4A. The phone number may correspond to any of first party device from the first party devices **102a-n**. In an embodiment, the user **108** selects a pre-stored phone number from the VOIP application **428**. As discussed with reference to FIG. 2, the representation of the visual IVR menu **302** and the one or more communication option **320a-n** can be provided on the display **402**. Subsequently, after detecting selection from the user **108**, the second party device **202** may be included in the call depending on the selection of the communication option.

In an embodiment, the Visuphone **106** may include a VOIP plug-in that monitors the incoming/outgoing calls to/from the VOIP application. Therefore, the VOIP plug-in may search each calling phone number of the first party device **102** in the database **414**. In case, the calling phone number is found in the database **414** and is associated with an audible IVR, then the VOIP plug-in may display the visual IVR menu corresponding to the audible IVR menu of the calling first party device phone number. In an embodiment, when the database does not include a match for the calling phone number of the first party device, then the communication device **104a** may request and/or receive the a visual IVR menu associated with the phone number from the first party device **102**.

FIG. 5 illustrates exemplary components of the communication device **104b** for implementing the Visuphone **106**, in accordance with another embodiment of the invention. The communication device **104b** includes a system bus **524** to connect the various components. Examples of the system bus **524** include, but are not limited to, a memory bus or memory controller, a peripheral bus, or a local bus using any of a variety of bus architectures. As discussed with reference to FIG. 1B, the communication device **104b** can be a computing device such as, but not limited to, a personal computer, a laptop, a mobile phone, a smart-phone, and so forth. The communication device **104b** can connect to the network **114** through a network interface **510**. Further, the communication device **104b** can connect to the PSTN **110** through the gateway **112** and the network **114** through the network interface **510**. An Input/Output (IO) interface **512** of the communication device **104b** may be configured to connect external or peripheral devices such as a mouse **514**, a keyboard **516**, a speaker **518**, a camera **520**, and a microphone **522**. Although not shown, various other devices such as a hard disk, a Universal Serial Bus (USB) device or others can be connected through the IO interface **512** to the communication device **104b**. A person skilled the art will appreciate that although not described, various other types of devices capable of voice and/or data communication can be connected to the communication device **104b**.

The communication device **104b** includes a display interface **502** to connect to a display **508**. The display interface **502**

can be for example, a video adapter. The display 508 outputs graphical information to the user 108. In an embodiment of the invention, the display 508 includes a touch sensitive screen. Therefore, the user 108 can provide inputs to the communication device 104b by touching display 508 or by scrolling and pointing with the mouse 514 and a click. A memory 506 of the communication device 104b may store various programs, data and/or instructions that can be executed by a processor 504. Examples of the memory 506 include, but are not limited to, a Random Access Memory (RAM), a Read Only Memory (ROM), a hard disk, and so forth. A person skilled in the art will appreciate that other types of computer-readable media which can store data that is accessible by a computer, such as magnetic cassettes, flash memory cards, digital video disks, and the like, may also be used by the communication device 104b. The memory 506 may include Operating System (OS) (not shown) for the communication device 104b to function. Further, the memory 506 may include other applications that enable user 108 to communicate/interact with the first party devices 102a-n. Examples of other applications include, but are not limited to, Skype, Google Talk, Magic Jack, and so forth. Other applications may be software or firmware stored on the communication device 104b.

Further, the memory 506 may include the Visuphone 106 for receiving a call from the first party devices 102a-n. Further, the Visuphone 106 is capable of presenting the visual IVR menu 302 corresponding to the audible IVR menu of a calling first party device 102 as discussed with reference to FIG. 3. Furthermore, the Visuphone 106 may display one or more communication options 320a-n on the display 508 of the communication device 104b. The Visuphone 106 may further request and/or receive information from the calling first party device 102 after establishing a communication session. The Visuphone 106 may be an application stored as a software or firmware on the communication device 104b. The Visuphone 106 may establish the communication session with the calling first party device 102 when the user 108 accepts the call. Further, the Visuphone 106 may include one or more second party 202 in a conference call by selecting a 'conferencing' option of the communication options 320a-n. The memory 506 further includes a database 414 for storing visual IVR menus associated with each of plurality of first party devices 102a-n. As discussed in FIGS. 4A and 4B, the phone numbers associated with the first party devices 102a-n are stored in the database 414 in memory 506 of the communication device 104b.

Depending on the complexity or size of the first party devices, the visual IVR menu 302 may have various nodes. For example, an organization with 50 departments may have more menu options or nodes than that of an organization with 10 departments. Further, the display area of display 508 may be limited. As a result, all the nodes of the visual IVR menu 302 may not be displayed together on display 508. In such a case, the Visuphone 106 is configured to allow the user 108 to navigate by scrolling horizontally and/or vertically to view nodes on the visual IVR menu 302. Moreover, the user 108 can search for a desired option from the visual IVR menu 302. Subsequently, after the user 108 selects a desired option from the visual IVR menu 302, a connection is established between the communication device 104b and the calling first party device 102 based on the selected option from the visual IVR menu 302.

Another embodiment of the invention allows the user to select one or more options of the visual IVR menu 302 using car display like GPS display. Hands-free cell phone system is used in many cars as a separate device or as an integrated

system in the car. These devices allow the user to talk with the cell phone without holding the cell phone in his hands. Some devices are using the car speakers for the phone call. In many cases, the hands-free system can use a display screen in the car like GPS screen or other display. Following voice menu while driving might not be the optimal way to use hands-free cell phone system. In some cases, selecting an option from a visual IVR menu 302 is preferred. While driving or stopping in red light, it might be easier to use larger display like the GPS display in the car. The display can present the visual IVR menu when the first party devices 102a-n calls the communication device 104a and the user can select the option from the visual IVR menu 302. The computing engine to support the visual IVR menu 302 could be embedded in the car GPS system or in another controller that have access to the car display. Once the system recognizes a first party device 102 of the call to be an IVR supported device then it will access the database, and pull out the representation of one or more first party devices and display. Accordingly all the other features of the Visuphone 106 could be incorporated.

Another embodiment of the invention allow visual IVR menu for calls made from a conventional home telephone. FIG. 6 illustrates the presentation of the visual IVR menu when a phone connection is associated with a wide band internet 'smart' modem, in an embodiment of the invention. A phone 604 connected to a Public Switched Telephone Network (PSTN) 608 and through a gateway 616 to the Internet network 618 is shown in FIG. 6. A first party device 102a can call a phone number of the phone 604. The network 618 may be any service provider that provides services, for example, but not limited to, telephone services, cell phone services, wireless services, Internet services, cable television services, or various combinations of the above or other type of services. An embodiment of the invention allow visual IVR menu for calls received at a conventional home telephone.

Further, the connection to the network 618 is associated with a wide band Internet 'smart' modem 606. The phone 604 may be a regular phone, such as a landline phone or a cordless landline phone. The modem 606 may be a Digital Subscriber Link (DSL) modem or a cable modem that connects the home device to the Internet and/or computer network. The modem 606 is connected to a service provider, and can provide the home devices with telephone, Internet and television services. The modem 606 may provide both wired and wireless connections. As shown with reference to FIG. 6, the modem 606 provides the home with the Internet through wire 610 to a computer 602, or through a Wi-Fi connection. The modem 606 comprises the ability to detect and recognize the calls received by the phone 604. The phone numbers received by the phone 604 to establish connection are then compared with phone numbers stored in a database, such as visual IVR menu database 414. Therefore, in case the calling phone number corresponds to the first party device 102a with an audible IVR menu, and also when associated visual IVR menu exists then, the modem 606 may provide the visual IVR menu on the computer 602 connected to it. Moreover, the modem 606 may use private web sites to present the visual IVR menu or just provide the phone number of the calling first party device 102a to the computer 602. Thereafter, a software tool on the computer 602 may present the visual IVR menu on the screen of the computer 602.

Once the communication session is established between the first party device 102a and the phone 604, the 'smart' modem 606 will continue to monitor the numbers dialed or received by phone 604 to browse or advance the visual IVR menu accordingly. Furthermore, the numbers dialed or received may be stored for future processing such as high-

lighting previous selections in the visual IVR menu, providing customized visual IVR menu and so forth. The visual IVR menu system comprising computer 602 and Modem 606 may incorporate additional enhancements as presented before.

In another embodiment of the invention, a house television 612 may be used to present the visual IVR menu. In various houses modem 606 decodes television signals and transfers it to a set-top box 614 that provides signals to television 612. The visual IVR menu may be presented on a channel dedicated for IVR. Therefore, when phone 604 is used to receive a call, modem 606 can detect it and present the visual IVR menu corresponding to the phone number of the calling first party device 102a on the designated channel of the television 612. The modem 606 may further display one or more communication options 320a-n on the designated channel of the television 612. Further, all the options described before can be provided now using the screen of the television 612 for the visual IVR menu. The caller selection can be done by using the simple phone 604 or alternatively using the TV 612, the set top box 614 remote control. Further, television 612 screen may be used to present the visual IVR menu in a few alternatives ways. For example, a device provided by a company named RokuInc., allows streaming of content from the Internet to television. Most set-top boxes now have an Internet connection or telephone connections. Furthermore, various devices such as some Digital Versatile Disc (DVD) players, and video game players or controllers such as Xbox or Playstation, can be connected to the Internet. Each of those devices may allow the 'smart' modem 606 to provide a visual IVR menu and/or the one or more communication options 320a-n on the screens of the television 612.

FIG. 7 illustrates a flowchart diagram for providing enhanced telephony, in accordance with an embodiment of the invention. The first party devices 102a-n may call a phone number of the communication device 104. The communication device 104 may receive a call from the phone number of the first party devices 102a-n. The user 108 may use the communication device 104 to connect or interact with the first party devices 102a-n and/or second party device 202. The first party devices 102a-n may include an audible IVR menu for interaction with the user 108. Further, the communication device 104 may include the Visuphone 106 to display a visual IVR menu 302 associated with a phone number of a first party device 102 from which a call is received. The Visuphone 106 may further display the one or more communication options 320a-n at the communication device 104, as discussed with reference to the FIG. 3. The Visuphone 106 may establish a communication session with the phone number of the calling first party device 102 by accepting the call. In an exemplary scenario, a user of the mobile phone receives a call from a bank, then 'conferencing' and 'call forwarding' options may also be displayed along with the visual IVR menu of the bank on the mobile phone. The user may select a 'conferencing' option to include another mobile device in the conference call. Similarly, the user may select the 'call forwarding' option to forward the call to another communication device or a server in the communication network 100.

At step 702, a call from a phone number of a first party device 102 such as a first party device 102a, is received. The call may be received by the Visuphone 106 of the communication device 104. The first party device 102a may initiate a call to the communication device 104 by dialing a phone number of the communication device 104. At step 704, the phone number of the first party device 102a is compared with a plurality of phone numbers stored at the communication device 104. The Visuphone 106 may compare the phone number of the first party device 102a with the stored phone

numbers. As discussed with reference to FIG. 4A, the database 414 may store the one or more phone numbers of the first party devices 102a-n. Further, the database 414 stores one or more visual IVR menus associated with the phone numbers of the first party devices 102a-n. In an embodiment, it may be checked whether a visual IVR menu associated with the phone number of the calling first party device 102a is present in the database 414 of the communication device 104. If the visual IVR menu is not present, the communication device 104 may receive the visual IVR menu associated with the first party device 102a from the first party device 102a. In an embodiment, the visual IVR menu associated with the first party device 102a may be received from the server.

At step 706, the visual IVR menu 302 associated with the calling first party device 102a is displayed. The visual IVR menu 302 may be displayed at the display 402 of the communication device 104, as shown in FIG. 4A. The visual IVR menu includes one or more graphics and/or text options corresponding to different nodes as shown in FIG. 3. At step 708, one or more communication options 320a-n is displayed. The one or more communication options 320a-n may be displayed at the display 402 of the communication device 104. Examples of the one or more communication options 320a-n include, but are not limited to, a conferencing option, a call forwarding option, a busy option, and so forth. At step 710, the user 108 of the communication device 104 may select a communication option of the displayed one or more communication options 320a-n. At step 712, a communication session is established based on the selection by the user 108. In an embodiment, the user 108 may select the 'conferencing' option, to establish the communication session between the first party device 102a, the communication device 104 and the second party device 202. Thereafter, all the three devices can communicate/interact with each other and may request/receive information from each other. In another embodiment, the user 108 may forward the call of the first party device 102a to another communication device of the communication network 100 by selecting the 'call forwarding' option. In an embodiment, the call may be forwarded to a server of the communication network 100. In another embodiment, the user 108 may select the 'busy' option when the user 108 cannot attend the call. Selecting the 'busy' option by the user may send a predefined audio/text message to the calling first party device 102a.

In another embodiment of the invention, a method is disclosed for displaying a visual IVR menu associated with a phone number of a first party device from which a call is received, at the communication device.

In an embodiment of the invention, more than one visual IVR menus associated with the phone numbers of the first party devices may be displayed at a communication device. In an embodiment, the Visuphone may display the one or more visual IVR menus at the communication device. In another embodiment of the invention, the user may request information from more than one first party device simultaneously. The user may interact with more than one visual IVR menus associated with different first party devices. In an embodiment, the one or more visual IVR menus may be associated with the second party device. For example: a user receives a call from an insurance department of a bank offering some insurance policy to the user. When the user accepts the call a visual IVR menu associated with the bank with the insurance department highlighted is displayed on the screen of the communication device. During the call, if the user wish to check his/her account balance to take a decision regarding insurance policies. The user may check his/her account balance by selecting the personal banking option from the visual IVR

15

menu of the bank. As soon as the user selects this option another visual IVR menu of the personal banking will be displayed on the screen of the communication device. Thereafter, the user may simultaneously interact with both the visual IVR menus.

In an embodiment of the invention, the user may request information from more than one first party device simultaneously. The user may interact with more than one visual IVR menus associated with different first party devices. For example: a user gets a call from a restaurant offering different types of cuisine. When the user accepts the call a visual IVR menu associated with the restaurant is displayed at the screen of the communication device. During the call, if the user wishes to check menus of two or more cuisines, the user may select from the main visual IVR menu of the restaurant. Based on the selection by the user, the two or more visual IVR menus may be displayed at the communication device. Thereafter, the user may simultaneously interact with the displayed visual IVR menus.

An aspect of the invention is to provide the visual IVR menu when the call is forwarded from one first party device to another.

Another aspect of the invention is to provide visual IVR menus on receiving a call from the first party device on electronic devices with screens that are connected to Visu- phone.

Yet another aspect of the invention is that the user may involve other one or more users or communication devices in a call from a first party device. Thereafter, the user, the another user may interact with the first party device in a conference call. In an embodiment, the user may leave the conference call in between the call.

Embodiments of the invention are described above with reference to block diagrams and schematic illustrations of methods and systems according to embodiments of the invention. It will be understood that each block of the diagrams and combinations of blocks in the diagrams can be implemented by computer program instructions. These computer program instructions may be loaded onto one or more general purpose computers, special purpose computers, or other programmable data processing translator to produce machines, such that the instructions which execute on the computers or other programmable data processing translator create means for implementing the functions specified in the block or blocks. Such computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including instruction means that implement the function specified in the block or blocks.

While the invention has been described in connection with what is presently considered to be the most practical and various embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims. The invention has been described in the general context of computing devices, phone and computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, characters, components, data structures, etc., that perform particular tasks or implement particular abstract data types. A person skilled in the art will appreciate that the invention may be practiced with other computer system configurations, including hand-held devices, multiprocessor systems, microprocessor-based or

16

programmable consumer electronics, network PCs, mini-computers, mainframe computers, and the like. Further, the invention may also be practiced in distributed computing worlds where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing world, program modules may be located in both local and remote memory storage devices.

This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope the invention is defined in the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Embodiments of the invention are described above with reference to block diagrams and schematic illustrations of methods and systems according to embodiments of the invention. It will be understood that each block of the diagrams and combinations of blocks in the diagrams can be implemented by computer program instructions. These computer program instructions may be loaded onto one or more general purpose computers, special purpose computers, or other programmable data processing translator to produce machines, such that the instructions which execute on the computers or other programmable data processing translator create means for implementing the functions specified in the block or blocks. Such computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including instruction means that implement the function specified in the block or blocks.

While the invention has been described in connection with what is presently considered to be the most practical and various embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims. The invention has been described in the general context of computing devices, phone and computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, characters, components, data structures, etc., that perform particular tasks or implement particular abstract data types. A person skilled in the art will appreciate that the invention may be practiced with other computer system configurations, including hand-held devices, multiprocessor systems, microprocessor-based or programmable consumer electronics, network PCs, mini-computers, mainframe computers, and the like. Further, the invention may also be practiced in distributed computing worlds where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing world, program modules may be located in both local and remote memory storage devices.

This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope the invention is defined in the claims, and may include other examples that

occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

The invention claimed is:

1. A communication device comprising:
 - (a.) a processor; and
 - (b.) a memory coupled to said processor, said memory comprising:
 - instructions executable by the processor for allowing access to a database comprising one or more visual Interactive Voice Response (IVR) menus associated with each of a plurality of phone numbers of one or more first party devices;
 - means for receiving a call from a first party device from the one or more first party devices;
 - means for comparing a phone number of the calling first party device with the plurality of phone numbers stored in the database, and retrieving from the database a visual IVR menu associated with the phone number of the calling first party device; and
 - means for displaying the retrieved visual IVR menu.
2. The communication device of claim 1 further comprising:
 - means for displaying one or more communication options;
 - means for selecting, by a user, a communication option from the displayed one or more communication options; and
 - means for establishing a communication session with at least one second party device based on the selection.
3. The communication device of claim 2 further comprising means for receiving, from the calling first party device, the visual IVR menu associated with the phone number of the calling first party device.
4. The communication device of claim 2, wherein the second party device is a first party device.
5. A communication device comprising:
 - a processor; and
 - a memory coupled to the processor, the memory comprising:
 - (a.) a database comprising one or more visual Interactive Voice Response (IVR) menus associated with each of a plurality of phone numbers of one or more first party devices;
 - (b.) instructions executable by the processor for receiving a call from a first party device from the one or more first party devices;
 - (c.) instructions executable by the processor for comparing a phone number of said first party device with phone numbers stored in the database, and retrieving from the database a visual IVR menu associated with the phone number of the first party device; and
 - (d.) instructions executable by the processor for sending to be displayed, said visual IVR menu.
6. The communication device of claim 5, wherein the memory further comprises instructions executable by the processor for:
 - displaying, at the communication device, one or more communication options;
 - selecting, by a user, a communication option from the displayed one or more communication options; and

establishing a communication session with at least one second party device based on the selection.

7. The communication device of claim 6, wherein the one or more communication options comprises a conferencing option for connecting the at least one second party device to the communication session.

8. The communication device of claim 7, wherein the one or more communication options further comprises a call forwarding option for directing the call of the first party device phone number to the at least one second party device.

9. The communication device of claim 6, wherein the memory further comprises instructions executable by the processor for displaying the visual IVR menu associated with the phone number of the second party device.

10. The communication device of claim 5, wherein the memory further comprises instructions executable by the processor for receiving, from the first party device, the visual IVR menu associated with the phone number of the first party device.

11. A method for providing enhanced telephony using communication device, the communication device comprising a processor and a memory coupled to the processor, the method comprising:

receiving, at the communication device, a call from a first party device having first party phone number, the memory of the communication device comprises one or more visual Interactive Visual Response (IVR) menus associated with each of a plurality of phone numbers of first party devices; and

in response to receiving the call from the first party device, comparing said first party phone number using said processor with said one or more visual Interactive Visual Response (IVR) menus, and providing to be displayed a visual IVR menu associated with said first party phone number.

12. The method of claim 11 further comprising: displaying, at the communication device, one or more communication options;

selecting, by a user, a communication option from the displayed one or more communication options; and establishing a communication session with at least one second party device based on the selection.

13. The method of claim 12, wherein the one or more communication options comprises a conferencing option for connecting the at least one second party device to the communication session.

14. The method of claim 13, wherein the one or more communication options further comprises a call forwarding option for directing the call of the first party device phone number to the at least one second party device.

15. The method of claim 12 further comprising receiving, at the communication device, a visual IVR menu associated with a phone number of the second party device.

16. The method of claim 15 further comprises displaying the visual IVR menu associated with the phone number of the second party device.

17. The communication device of claim 11 further comprising receiving, from the first party device, the visual IVR menu associated with the phone number of the first party device.

18. A Non transitory tangible computer readable medium comprising instructions for the execution according to claim 11.