

station **12b** and the IP address of home agent **16**. This has the effect of shifting the mobile station's home IP address from the home agent **16** to the foreign agent **18**.

The teachings of the invention recognize that home agents, such as home agents **16**, may often be used to provide access to a plurality of networks **26, 28**, one example of which is a virtual private network. A virtual private network generally refers to a private network that uses a public network to connect remote sites or users together. For example, home agent **16** may be operated by a service provider, such as Verizon, which in turn offers virtual private network services to various companies. In one example, Federal Express may provide a home web page associated with a virtual private network, such as virtual private network **26**, to its mobile users through a Verizon home agent **16**, while UPS provides a different home web page associated with a virtual private network, such as virtual private network **28**. By allowing appropriate selection of a particular virtual private network **26, 28** associated with a home agent **16**, a Federal Express or UPS employee may reap the advantages of the Mobile IP protocol and maintain constant connectivity with the virtual private networks of their respective companies, all through the same home agent.

The teachings of the invention recognize that home agent **18** may be configured to select an appropriate virtual private network **26, 28** for a mobile station **12** by allowing the home agent **16** to respond with the correct IP address of the virtual private network in a response to a registration request.

In one example, once a registration request for a mobile station has been received, home agent **16** selects the correct virtual private network **26, 28**. Once the correct virtual private network has been selected, the address allocation for the end user is performed in accordance with its virtual private network membership. Once this is completed, home agent **16** maps the virtual private network **26, 28** to a local IP address, and uses this in the registration reply response back to the foreign agent **18**. All subsequent data traffic from foreign agent **18** to the home agent **16** will then use the new local IP address as the end point. Home agent **16** then classifies these back to the correct virtual private network membership. Example details associated with example embodiments of such a method and system are described in greater detail below in conjunction with FIGS. **2** through **4**.

FIG. **2** is a block diagram of home agent **16** according to the teachings of the invention. As illustrated, home agent **16** includes a virtual private network functionality block **30** and an other home agent functionality block **32**. In general, virtual private network functionality block **30** contains functionality sufficient to allow appropriate selection of the virtual private network or enterprise **26, 28** to which a mobile user seeks to connect. Other home agent functionality block **32** provides all other functionality associated with home agent **16** implementing the Mobile IP Protocol.

Although illustrated as two separate functional blocks for simplicity, it will be understood that functions of each block **30** and **32** may be combined into a single functional unit. Further, home agent **16**, including functional blocks **30** and **32**, may be implemented in hardware, software, firmware, or in other suitable manners. In one particular example, functionality within a private block **30** and **32** is provided through software encoded in media, such as RAM, ROM, or other suitable media. Example functions associated with virtual private network functionality block **30** are described in greater detail below in conjunction with FIG. **3**.

The teachings of the invention recognize that in order to support overlapping of IP addresses per enterprise **26, 28**—multiple enterprise users sharing the same service pro-

vider home agent **16**—a mechanism is needed to distinguish packets in foreign agent **18** for each enterprise **26, 28**. According to one embodiment, this is achieved by using different IP addresses on home agent **16** corresponding to each enterprise **26, 28**. In certain implementations, this results in the use of one mobile IP tunnel between foreign agent **18** and home agent **16** per enterprise **26, 28**.

Different IP addresses for home agent **16** for each enterprise may be configured, in one example, by configuring a loopback interface **34** on the home agent **16**. Multiple IP addresses may then be configured using the loopback interface. According to one implementation, the loopback interface **34** is configured such that it is always up, although the loopback interface could be configured in other manners.

As an example, a service provider abc.com may have two customers—xyz.com and mnp.com. On the abc.com home agent **16**, there is a loopback interface **34** with IP addresses of IP-1 and IP-2 for xyz.com and mnp.com, respectively, configured under the loopback interface **34**. A mobile IP tunnel is opened at the home agent **16** for abc.com with a tunnel source address of IP-1 and that for mnp.com is IP-2.

FIG. **3** is a flowchart illustrating a method **100** for providing virtual private network functionality via a home agent, such as home agent **16**. The method begins at step **102**. At step **104** a mobile subscriber, such as mobile subscriber **12a, 12b** connects to a home agent to register. This registration occurs by a foreign agent sending a registration request to an associated home agent. At step **106**, the home agent determines the virtual private membership of the mobile subscriber. One example of this determination is based on the user ID of the mobile subscriber, which is included within the registration request sent at step **104**. However, other modes of determining the virtual private membership of the mobile subscriber can be used.

At step **108** the IP address of the virtual private network is allocated based upon the membership of the mobile subscriber. In addition, the IP address associated with the virtual private network to which the mobile subscriber belongs is determined. At step **110** the mobile subscriber is mapped to the allocated IP address. This mapping allows subsequent transmissions from the mobile subscriber to be sent to the allocated IP address. Alternatively, rather than allocating a particular IP address associated with the virtual private network, a tag may be utilized to direct transmissions to the appropriate virtual private network. This tag may be an inline field within one of the packet headers that is communicated between the foreign agent (PDSN) and the home agent, and used for identification of the virtual private network.

At step **112** the mapping of the indicated IP address (or other suitable identifier) is transmitted to the foreign agent. At step **114** packets transmitted by the foreign agent from the mobile subscriber include the allocated IP address or tag. Thus, when received by the home agent, the packets can be directed to the appropriate virtual private network. The method concludes at step **116**.

Thus, according to one embodiment of the invention, the capability to provide virtual private network services employed with a home agent in an existing mobile IP network is provided, by allowing the home agent to map a local end-point IP address to the virtual private network membership. In one embodiment, the deployment of virtual private network services on the home agent is accomplished without changes to the foreign agent, or any protocol changes.

FIG. **4** is a call flow diagram illustrating portions of an example call flow of the above described invention associated with providing access to a virtual private network according to the teachings of the invention. At step **210** through **240**, the

5

mobile node, which belongs to enterprise 1 establishes a PPP session with the PDSN, which in this example hosts the foreign agent functionality discussed. A PPP session is the point-to-point protocol used between the end-mobile user and the PDSN. At step 250 the mobile node sends a mobile IP registration request with, in one example, the home agent address set to 0.0.0.0, corresponding to a dynamic home agent, to the PDSN over its R-P session. At step 260 the PDSN forwards the mobile IP registration request to the home agent.

At steps 270 through 310, the home agent receives the mobile IP registration request. It parses the network access identifier inside the message and determines the virtual routing function of the mobile node based on its realm, which is enterprise 1, in this example. The home agent then performs the user authentication and allocates the IP address. The home agent also creates a binding for the mobile node and populates the virtual routing function's specific data structures, such as route entry into a route table of virtual routing functions.

At step 320 the home agent sends the mobile IP registration reply to the home agent. At steps 330-350 the home agent establishes, in one embodiment, a mobile IP tunnel between the foreign agent and the home agent. The endpoint of the tunnel on the home agent is the IP address of enterprise 1, rather than the IP address of the ingress interface in the mobile IP registration request.

Although the above call flow diagram illustrates one example call flow, it should be understood that numerous variations on this call flow may be made. Further, although the present invention has been described with several embodiments, a myriad of changes, variations, alterations, transformations, and modifications may be suggested to one skilled in the art, and it is intended that the present invention encompass such changes, variations, alterations, transformations, and modifications as they fall within the scope of the appended claims.

What is claimed is:

1. A method for providing access to a network by a home agent in a Mobile IP environment comprising: providing a home agent operable to receive a registration request from a foreign agent and negotiate conditions of attachment of a mobile node to the foreign agent and further operable to store an IP address of the foreign agent in response to the negotiated conditions; receiving, at the home agent, from the foreign agent, a registration request for a mobile node; determining, by the home agent, a virtual private network membership of the mobile node based on a characteristic associated with the mobile node; mapping the mobile node to an identifier associated with the home agent and transmitting the mapping to the foreign agent, the identifier indicative of the virtual private network membership of the mobile node; and receiving packets containing the identifier from the foreign agent and in response directing the packets to an IP address associated with the virtual private network.

2. The method of claim 1, wherein the network is a virtual private network.

3. The method of claim 1, wherein the characteristic associated with the mobile node is a user ID for the network.

4. The method of claim 1, wherein the identifier comprises a tag.

5. The method of claim 1, wherein the identifier comprises an IP address of the network to which the mobile node is a member.

6. The method of claim 1, wherein the foreign agent comprises a PDSN.

7. The method of claim 1, wherein the home agent comprises a plurality of home agents.

6

8. The method of claim 2, and further comprising providing an IP address for the virtual private network by configuring a loopback interface in the home agent.

9. The method of claim 1, wherein the identifier comprises a combination of a tag and an IP address of the network to which the mobile node is a member.

10. A home agent comprising: logic encoded in media operable to: receive a registration request from a foreign agent and negotiate conditions of attachment of a mobile node to the foreign agent and further operable to store an IP address of the foreign agent in response to the negotiated conditions; determine a virtual private network membership of the mobile node based on a characteristic associated with the mobile node; map the mobile node to an identifier associated with the home agent and transmit the mapping to the foreign agent, the identifier indicative of the virtual private network membership of the mobile node; and receive packets containing the identifier from the foreign agent and in response direct the packets to an IP address associated with the virtual private network.

11. The home agent of claim 10, wherein the network is a virtual private network.

12. The home agent of claim 11, wherein the characteristic associated with the mobile node is a user ID for the virtual private network.

13. The home agent of claim 11, wherein the identifier comprises a tag.

14. The home agent of claim 11, wherein the identifier comprises an IP address of the virtual private network to which the mobile node is a member.

15. The home agent of claim 10, wherein the foreign agent comprises a PDSN.

16. The home agent of claim 10, wherein the home agent comprises a plurality of home agents.

17. The home agent of claim 11, and further comprising a loopback interface coupled to the media and operable to provide an IP address for the virtual private network.

18. The home agent of claim 10, wherein the identifier comprises a combination of a tag and an IP address of the network to which the mobile node is a member.

19. A Mobile IP network comprising:

a mobile node;

a foreign agent; and

a home agent operable to:

receive a registration request from the foreign agent and negotiate conditions of attachment of the mobile node to the foreign agent and further operable to store an IP address of the foreign agent in response to the negotiated conditions;

determine a virtual private network membership of the mobile node based on a characteristic associated with the mobile node;

map the mobile node to an identifier associated with the home agent and transmit the mapping to the foreign agent, the identifier indicative of the virtual private network membership of the mobile node; and

receive packets containing the identifier from the foreign agent and in response direct the packets to an IP address associated with the virtual private network.

20. The Mobile IP network of claim 19, wherein the characteristic associated with the mobile node is a user ID for the virtual private network.

21. The Mobile IP network of claim 19, wherein the identifier comprises a tag.

22. The Mobile IP network of claim 19, wherein the identifier comprises an IP address of the virtual private network to which the mobile node is a member.

7

23. The Mobile IP network of claim 19, wherein the foreign agent comprises a PDSN.

24. The Mobile IP network of claim 19, and further comprising the virtual private network.

25. The Mobile IP network of claim 19, wherein the home agent comprises a loopback interface operable to provide an IP address for the virtual private network.

26. The Mobile IP network of claim 19, wherein the home agent comprises a plurality of home agents.

27. The Mobile IP network of claim 19, wherein the identifier comprises a combination of a tag and an IP address of the network to which the mobile node is a member.

28. A method for providing a virtual network by a home agent in a Mobile IP environment comprising:

establishing communication between a mobile subscriber and a foreign agent;

providing a home agent operable to receive a registration request from the foreign agent and negotiate conditions of attachment of the mobile subscriber to the foreign agent and further operable to store an IP address of the foreign agent in response to the negotiated conditions;

receiving at the home agent, from the foreign agent, a registration request for the mobile subscriber;

determining, by the home agent, a virtual private network membership of the mobile subscriber based on a characteristic associated with the mobile subscriber;

mapping the mobile subscriber to an identifier associated with the home agent and transmitting the mapping to the foreign agent, the identifier indicative of the virtual private network membership of the mobile subscriber;

transmitting, to the foreign agent, packets from the mobile subscriber directed to the home agent;

forwarding, by the foreign agent, the transmitted packets to the home agent; and

identifying, by the home agent, the identifier in the received packets, and in response, directing the received packets to an IP address associated with the virtual private network.

8

29. The method of claim 28, wherein the characteristic associated with the mobile subscriber is a user ID for the virtual private network.

30. The method of claim 28, wherein the identifier comprises a tag.

31. The method of claim 28, wherein the identifier comprises an IP address of the virtual private network to which the mobile subscriber is a member.

32. The method of claim 28, wherein the foreign agent comprises a PDSN.

33. The method of claim 28, wherein the home agent comprises a plurality of home agents.

34. The method of claim 28, wherein the home agent comprises a loopback interface operable to provide an IP address for the virtual private network.

35. The method of claim 28, wherein the identifier comprises a combination of a tag and an IP address of the network to which the mobile subscriber is a member.

36. A home agent for use in providing a virtual private network comprising:

structure operable to receive a registration request from a foreign agent and negotiate conditions of attachment of a mobile node to the foreign agent and further operable to store an IP address of the foreign agent in response to the negotiated conditions;

means for determining a virtual private network membership of the mobile node based on a characteristic associated with the mobile node;

means for mapping the mobile node to an identifier associated with the home agent in transmitting the mapping to the foreign agent, the identifier indicative of the virtual private membership of the mobile node; and

means for receiving packets containing the identifier from the foreign agent and in response directing the packets to an IP address associated with the virtual private network.

* * * * *